



Typ	Lengte mm	Breedte loopvlak mm	Breedte rijplaat mm	Hoogte draagbalk mm	Hoogte rand mm	Gewicht per stuk kg	Laadvermogen per stuk kg	Bestelnr.
KANAALRAILS								
VSR 47	1500	164	224	47	44	4	1050	1015022-R
	1800	164	224	47	44	5	890	0818022-R
	2100	164	224	47	44	6	700	0721022-R
	2400	164	224	47	44	6	550	0524022-R
	2700	164	224	47	44	7	420	0427022-R
	3000	164	224	47	44	8	340	0330022-R
	3300	164	224	47	44	9	230	0233022-R
	3600	164	224	47	44	10	190	0136022-R
Opklapbare uitvoering tegen meerprijs verkrijgbaar								RKV47
VSR 55	1500	235	320	55	50	8	1750	1715032-R
	1800	235	320	55	50	10	1450	1418032-R
	2100	235	320	55	50	12	1250	1221032-R
	2400	235	320	55	50	13	1100	1124032-R
	2700	235	320	55	50	15	850	0827032-R
	3000	235	320	55	50	17	700	0730032-R
	3300	235	320	55	50	18	590	0533032-R
	3600	235	320	55	50	20	450	0436032-R
Opklapbare uitvoering tegen meerprijs verkrijgbaar								RKV55
STAANDE RAILS								
VSR 47	1500	164	224	47	44	4		15022-R-ST
	1800	164	224	47	44	5		18022-R-ST
	2100	164	224	47	44	6		21022-R-ST
	2400	164	224	47	44	6		24022-R-ST
	2700	164	224	47	44	7		27022-R-ST
	3000	164	224	47	44	8		30022-R-ST
	3300	164	224	47	44	9		33022-R-ST
	3600	164	224	47	44	10		36022-R-ST
VSR 55	1500	235	320	55	50	8		15032-R-ST
	1800	235	320	55	50	10		18032-R-ST
	2100	235	320	55	50	12		21032-R-ST
	2400	235	320	55	50	13		24032-R-ST
	2700	235	320	55	50	15		27032-R-ST
	3000	235	320	55	50	17		30032-R-ST
	3300	235	320	55	50	18		33032-R-ST
	3600	235	320	55	50	20		36032-R-ST
STAANDE RAILS MET MOTORWIP								
VSR 47	600	164	224	47	44	6		6022-R-SW
	900	164	224	47	44	7		9022-R-SW
	1200	164	224	47	44	8		12022-R-SW
	1500	164	224	47	44	8		15022-R-SW
	1800	164	224	47	44	9		18022-R-SW
	2100	164	224	47	44	10		21022-R-SW
	2400	164	224	47	44	11		24022-R-SW
	2700	164	224	47	44	11		27022-R-SW

